



## Gulf Pride 4004 10W-40 4-Cycle Outboard Engine Oil

### Product Description

**Gulf Pride 4004 10W-40** is premium quality 4-cycle engine oil specially developed for the most modern high output gasoline powered, water cooled outboard, inboard/outboard and personal watercraft engines. It is specially developed to exceed the performance requirements of National Marine Manufacturers Association's specification NMMA FC-W® (Four Cycle-Water specification). This high quality oil is designed for the harsh operating conditions of marine environment and it provides excellent lubrication and protection against wear, deposits and rust & corrosion.

### Features & Benefits

- Exceptional shear stability provides protection against viscosity loss leading to superior wear protection of engines operating under high load/ high speed for extended period of time
- Advanced rust inhibitors guard against rust & corrosion even in marine salt water environment
- Good Low temperature fluidity assists easy cold start
- Active cleaning agents provide superior engine cleanliness

### Applications

- Recommended for and meets the warranty requirements of the following modern high output gasoline powered 4-cycle water cooled engines requiring NMMA FC-W® quality oil.
  1. Outboard Motors: Honda®, Mercury®, Yamaha®, Johnson®/Evinrude®, Bombardier/BRP®, Suzuki®, Nissan®, Tohatsu®
  2. Inboard/Outboard Motors: Mercruiser®, Volvo Penta®, OMC®, Chrysler® Marine, Crusader®, Marine Power®, Chevrolet®, Ford®
  3. Personal Watercraft: Honda®, Yamaha®, Bombardier/BRP® (Sea-Doo®), Polaris®

### Specifications, Approvals & Typical Properties

Cumple con las siguientes especificaciones		
NMMA FC-W <sup>®</sup> Registration Number: FB-44303J		
Propiedades típicas		
Parámetros de Prueba	Método ASTM	Valores Típicos
Color	Visual	Clara y brillante
Viscosity @ 40 °C, cSt	D 445	111.8
Viscosity @ 100 °C, cSt	D 445	15.07
Viscosity Index	D 2270	140
Flash Point, °C	D 92	250
Pour Point, °C	D 97	-27
TBN, mg KOH/g	D 2896	7.77
Density @ 15°C, Kg/l	D 1298	0.8828
Sulphated Ash, %wt	D 874	0.84
Viscosity Aparente (C.C.S) @-10 °c	D 5293	1793

January 2018

Las propiedades arriba indicadas son valores típicos que pueden tener mínimas variaciones, las mismas que no afectan la calidad del producto y son propias del normal proceso de producción. Esta información está basada en datos históricos y no constituye una garantía del desempeño del producto. Se recomienda seguir las recomendaciones del fabricante respecto de los niveles de calidad y grados de viscosidad requeridos. La hoja de seguridad de este producto puede ser consultada en nuestra página web [www.lubrisa.com/](http://www.lubrisa.com/) [www.gulfoilltd.com](http://www.gulfoilltd.com) o consultando con su Distribuidor Autorizado GULF más cercano.

Lubricantes Internacionales S.A. LUBRISA se reserva el derecho de modificar o cambiar los productos y especificaciones aquí detalladas sin previo aviso.